

SET-UP SHEET

XRAY XB4'26

RACE	Mibosport International	
TRACK	Mibosport	
NAME	Max	DATE

LAPS		BEST LAP TIME	sec
QUALIFYING POSITION	8	FINAL POSITION	6

TRACK		
SIZE	☐ OPEN	☐ MEDIUM
TRACTION	☐ VERY-LOW	☐ MEDIUM
SURFACE	☐ SMOOTH	☐ MEDIUM
TYPE	☐ CLAY	☒ CARPET
CONDITION	☐ BLUE GROOVE	☐ HARD PACKED
	☐ GLUED	☐ DUSTY

DIFFERENTIAL TYPE		
FRONT ↓	MIDDLE ↓	REAR ↓
GEAR ☒ DIFF	SLIPPER ☒ SOLID	GEAR ☒ DIFF
ACTIVE ☐ DIFF	ACTIVE ☐ DIFF	ACTIVE ☐ DIFF
60° 90° 120°	60° 90° 120°	60° 90° 120°
OIL 30k	OIL	OIL 40k
SATELLITE GEARS		
COMP ☐	COMP ☐	COMP ☐
STEEL ☒ O-RING	STEEL ☐ O-RING	STEEL ☒ O-RING
40T ☒ 41T	CROWN GEAR	40T ☒ 41T

CENTRAL SLIPPER & ONE-WAY SETTING	
SLIPPING	ONE-WAY TIGHTNESS
11.9 mm	1 CW TURN (BASIC SETUP)

GEARING	
PINION 18	SPUR GEAR 78

FRONT	SHOCKS	REAR
4	SPRINGS	4
425	OIL	350
2 HOLES ☒	0.6mm	2 HOLES ☒
0.8mm	2.0mm	0.8mm
2.5mm	2.5mm	2.5mm
COMPOSITE	0mm	COMPOSITE
ALU	-2mm	ALU
-4mm	COLLAR	-4mm
-6mm	BALL JOINT	-6mm
+4mm +2mm 0mm		0mm +2mm +4mm

FRONT	ANTI ROLL BAR	REAR
2	THICKNESS	2

FRONT	TIRES	REAR
Shard	BRAND	Cactus
Handout	COMPOUND	Handout
Handout	INSERTS	Handout
HUDY	WHEELS	HUDY

ELECTRONICS		
MOTOR	Exalt 4.5T	ELC Nitride G2
SERVO	Savox 3262	Exalt 5200
BATTERY		

BODY	TOTAL WEIGHT
Dirt'25	/g

COMMENTS

FRONT	APPLIED	REAR
CASTER BLOCK	☐ MEDIUM	☐ MEDIUM
☐ HARD	☐ GRAPHITE	☐ HARD
☒ ALU	☒ ALU	☒ ALU
LONGER BUSHINGS	☐ UP	☐ UP
☒ DOWN	☐ DOWN	☐ DOWN
DRIVE SHAFT	CVD ☒ ECS	DRIVE SHAFT
Length 84 /mm		SHIM 1 /mm
SHIM 1 /mm		SHIM 0 /mm
SHOCK TOWER	☒ 5 DOT	☐ 5 DOT
☐ 3 DOT		☐ 3 DOT
ROLL ENTER		REAR UPRIGHT
LOWER SHOCK POSITION		☐ HIGH
DOWNSTOP		☒ LOW
		☒ EXTRA LOW
		#325341 ADJ. DRIVE AXLE
		DOWNSTOP

FRONT	SERVO SAVER	WING TYPE
CASTER	SOFT ☐	☒ Lush
☒ 6°	MEDIUM ☐	KIT ☒ THICK
☐ 7°	TIGHT ☒	WING POSITION
☐ 9°	MATERIAL	☐ UP
☐ 12°	KIT ☐	☐ MIDDLE
OFFSET	GRAPHITE ☒	☐ DOWN
1 /slots	BUMP STEER	OFFSET
	1 /mm	1 /slots

FRONT	ROLL CENTER	REAR
☐ 1°	☒ 0.5°	☐ 1°
☒ 0.5°		☒ 0.5°
ECCENTRIC BUSHINGS		DOWN ☐ UP ☒
		EXTRA UP #363300

FRONT	STEER. PLATE	REAR
FRONT TOE	HARD ☐	REAR TOE
1.5	GRAPHITE ☐	2
	ALU ☒	
SERVO WEIGHT	BUMP STEER	CARBON FOR REAR BRACE
STANDARD ☐	SHIM 1.5 mm	YES ☒ NO
LOW PROFILE ☒		REAR BRACE
FRONT BRACE		MEDIUM ☐
MEDIUM ☐		HARD ☒
HARD ☒		GRAPHITE ☐
GRAPHITE ☐		BATTERY SIZE
		STANDARD ☐
		LOWER ☒
		STAND OFF
		KIT ☒
		LONG ☐

FRONT	SHOCK CAP	FRONT DIFF HEIGHT	REAR DIFF HEIGHT	REAR CAMBER	SHOCK CAP
2	Previous	0	0	2	Previous
☒ KIT	☒ KIT	☒ KIT	☒ KIT	☒ KIT	☒ KIT
☐ ALU	☐ ALU	☐ ALU	☐ ALU	☐ ALU	☐ ALU
GLUING SIDEWALL	YES ☒ NO	DOWNSTOP	DOWNSTOP	DOWNSTOP	DOWNSTOP
YES ☒ NO		0	0	0	0
LENGTH	21.5 mm	LENGTH	25.7 mm	LENGTH	25.7 mm
UPSTOP	3	UPSTOP	3	UPSTOP	3
FRONT CAMBER	2	FRONT CAMBER	2	FRONT CAMBER	2
FRONT CAMBER	2	FRONT CAMBER	2	FRONT CAMBER	2
FRONT CAMBER	2	FRONT CAMBER	2	FRONT CAMBER	2

FRONT ARMS	BALANCE	STEER. FLEX	COOLING	BALANCE	REAR ARMS
MEDIUM ☐	10 g	KIT ALU FLEX	REAR ☒	10 g	MEDIUM ☐
HARD ☐		ALU FIX	NO ☐		HARD ☐
GRAPHITE ☒					GRAPHITE ☒
STEERING PLATE					ARMS TYPE
1 DOT ☐					STANDARD ☒
2 DOTS ☒					DISENGAGED ☐
3 DOTS ☐					TRANSMISSION
					STANDARD ☒
					SHORT ☐