

SET-UP SHEET

XRAY XB8E'26

RACE	Czech Open R1		
TRACK	RCDJ / MaxLand 1/8		
NAME	Max Gotzl	DATE	6.7.2026
TEMPERATURE AIR		TEMPERATURE TRACK	
LAPS	FINAL POSITION	BEST LAPTIME	RACE LENGTH
	1	/sec	/min

TRACKS			
SIZE	☐ OPEN	☒ MEDIUM	☐ TIGHT
TRACTION	☐ LOW	☒ MEDIUM	☐ HIGH
SURFACE	☐ SMOOTH	☒ MEDIUM	☐ BUMPY
TYPE	☐ HARD PACKED	☐ SOFT DIRT	☒ CLAY
	☐ GLUED	☐ BLUE GROVE	☐ ASTRO TURF
		☐ GRASS	
CONDITION	☐ DRY	☐ DUSTY	☐ WET
		☐ MUD	

DIFFERENTIAL			
CASE MATERIAL	FRONT	CENTER	REAR
	G	G	G
OIL	15k	15k	5k
CROWN GEAR	46		46
GEAR	2 ☒ 4		2 ☒ 4
PINION	13 ☐ 14		13 ☒ 14

GEARING			
MOTOR PINION	15	SPUR GEAR	46
	/T		/T
		COMP.	GRAPHITE
		☒	☒
		STEEL	☐

FRONT	SHOCKS	REAR
Emulsion	TYPE	Emulsion
4	SPRINGS	3
	MEMBRANE	
550	OIL	500
/cSt		/cSt
☐ 6 HOLES	☐ 1.1 mm	☐ 6 HOLES
☐ 8 HOLES	☐ 1.2 mm	☐ 8 HOLES
☐ 10 HOLES	☐ 1.3 mm	☐ 10 HOLES
	☐ 1.4 mm	
	OTHER	
5+2 HOLES	VALVE	5+2 HOLES
6+2 HOLES	1.5 mm	6+2 HOLES
8+2 HOLES	1.3 mm	8+2 HOLES
	1.4 mm	
	1.2 mm	
	1.3 mm	

FRONT	ANTI-ROLL BAR	REAR
2,2	THICKNESS	2,4
/mm		/mm

FRONT	TIRES	REAR
HotRace	BRAND	Bangkok V2
Soft	COMPOUND	Soft
HotRace	INSERTS	HotRace
HotRace	WHEELS	HotRace

ELECTRONICS	
MOTOR	Exalt 2050 kV
SPEEDO	Elceram Oxide 1/8
BATTERY TYPE	Exalt 6400 mAh
MID-SIZE BATTERY	FRONT ☒ SHORT BATTERY
MID-SIZE BATTERY	SHORT BATTERY
	REAR ☐

BODY		OTHER	TOTAL WEIGHT
EASY	EASY LIGHT		/g
☐	☒		

FRONT	REAR
STEERING BLOCK	UPRIGHT
MEDIUM ☐	MEDIUM ☐
HARD ☐	HARD ☐
GRAPHITE ☒	GRAPHITE ☒
UPPER ARM SHIM /mm	ALU #350908
0 ☐ 1 ☐ 1.5 ☒ 2 ☐	
UPPER ARM WING	
NONE ☒	
LEXAN ☐	
CARBON ☐	
UPPER SHOCK POSITION	
3 2 1	
FRONT LOWER SHOCK POSITION	
2 1	
LOWER ARM SHIM /mm	
0 ☒ 1 ☐ 1.5 ☐ 2 ☐	
FRONT DROOP	REAR DROOP
MEASURE UNDER WHEEL AXLE #107717 GAUGE	MEASURE UNDER WHEEL AXLE #107717 GAUGE

FRONT	REAR
UPPER ROLL CENTER	REAR WING
1° ☒ 0.5° ☐	COMPOSITE ☒
	LEXAN ☐
	OTHER ☐
CASTER SHIM	CUT OUT HOLES
0 1.0 1.0 2.0	REDUCE DOWNFORCE
UPPER ARM POSITION	
BUMP STEER SHIM	CARBON BRACE
STER. PLATE 0 /mm	WITHOUT ☒
STER. BLOCK 0 /mm	1-PIECE ☐
SHIMS PLACE ALWAYS UNDER	2-PIECES ☐
WHEELBASE SHIM POSITION	
0mm 2mm 4mm	
SHIMS BEHIND FRONT ARM	
WHEELBASE SHIM POSITION	
0mm 2mm 4mm	
SHIMS IN FRONT OF REAR ARM	
LOWER ROLL CENTER	
ECCENTRIC BUSHINGS	

FRONT	CHASSIS	REAR
1 FRONT TOE OUT	STEERING PLATE	3 REAR TOE IN
	CARBON ☐	
	ALU ☒	
	1 DOT ☐	
	2 DOTS ☐	
	3 DOTS ☐	
FRONT DRIVE SHAFT	WHEELBASE	
CVD ☒	0mm 1mm 2mm 3mm 4mm	
UNIVERSAL ☒	SHIMS IN FRONT OF UPRIGHT	
LENGTH /mm		
ACKERMANN 4 3 2 1		
GRAPHITE ☐		
MEDIUM ☐		
SERVO SAVER		
TIGHT ☒		
MEDIUM ☐		
SOFT ☐		
KIT ☐		
ALU ☒		
FRONT WING		
YES ☒ NO ☐		
TOP DECK		
COMPOSITE ☒		
CARBON ☐		
DRIVE SHAFT		
CVD ☒		
DOGBONE ☐		
REAR DRIVE SHAFT		
CVD ☒		
LENGTH /mm		

FRONT	REAR
FRONT CAMBER	REAR CAMBER
101 /mm	121 /mm
LENGTH	LENGTH
UPPER ARM	FRONT DIFF HEIGHT
SOFT ☒	
MEDIUM ☐	
GRAPHITE ☐	
LOWER ARM	REAR DIFF HEIGHT
SOFT ☐	
MEDIUM ☒	
GRAPHITE ☐	
RISE HEIGHT 23 /mm	RISE HEIGHT 27 /mm
	#107763 RISE HEIGHT GAUGE